



SAFETY DATA SHEET

1. Identification

Product identifier	CARUSOL® liquid permanganate
Other means of identification	-
SDS number	-
Recommended use	Water treatment. Wastewater treatment. Industrial use.
Recommended restrictions	Use in accordance with supplier's recommendations.
Manufacturer / Importer / Supplier / Distributor information	
Manufacturer/Supplier	CARUS CORPORATION
Address	315 Fifth Street, Peru, IL 61354, USA
Telephone	815 223-1500 - All other non-emergency inquiries about the product should be directed to the company
E-mail	salesmkt@caruscorporation.com
Website	www.caruscorporation.com
Contact person	Dr. Chithambarathanu Pillai
Emergency Telephone	For Hazardous Materials [or Dangerous Goods] Incidents ONLY (spill, leak, fire, exposure or accident), call CHEMTREC at CHEMTREC®, USA: 001 (800) 424-9300 CHEMTREC®, Mexico (Toll-Free - must be dialed from within country): 01-800-681-9531 CHEMTREC®, Other countries: 001 (703) 527-3887

2. Hazard(s) identification

Physical hazards	Oxidizing liquids	Category 2
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 1B
	Serious eye damage/eye irritation	Category 1
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger	
Hazard statement	May intensify fire; oxidizer. Harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation.	
Precautionary statement		
Prevention	Keep away from heat. Take any precaution to avoid mixing with combustibles. Keep/Store away from clothing//combustible materials. Use only outdoors or in a well-ventilated area. Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.	
Response	In case of fire: Use water for extinction. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing.	
Storage	Store locked up. Store in a well-ventilated place. Keep container tightly closed.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. Rinse container at least three times to an absence of pink color before disposing.	
Hazard(s) not otherwise classified (HNOC)	Not classified.	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Sodium permanganate	10101-50-5	19 - 21

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Get medical attention immediately.

Skin contact Take off immediately all contaminated clothing. (Caution: Solution may ignite certain textiles). Immediately flush skin with plenty of water. Get medical attention immediately. Wash contaminated clothing before reuse.

Contact with skin may leave a brown stain of insoluble manganese dioxide. This can be easily removed by washing with a mixture of equal volume of household vinegar and 3% hydrogen peroxide, followed by washing with soap and water.

Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids wide apart. Continue rinsing. Get medical attention immediately.

Ingestion Immediately rinse mouth and drink plenty of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately.

Most important symptoms/effects, acute and delayed Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Decomposition products are alkaline. Brown stain is insoluble manganese dioxide.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Flood with water from a distance, water spray or fog.

Unsuitable extinguishing media The following extinguishing media are ineffective: Dry chemical. Foam. Carbon dioxide (CO₂). Halogenated materials.

Specific hazards arising from the chemical May intensify fire; oxidizer. May ignite combustibles (wood, paper, oil, clothing, etc.). Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction. Oxidizing agent, may cause spontaneous ignition of combustible materials. By heating and fire, corrosive vapors/gases may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire-fighting equipment/instructions Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Dike fire control water for later disposal. Water runoff can cause environmental damage.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment. This product is miscible in water. Stop leak if possible without any risk. Dike the spilled material, where this is possible. Proceed with either of the following two options depending upon the size of the spill and the availability of the neutralizing agents:

Option # 1: Dilute to approximately 6% with water, and then reduce with sodium thiosulfate, a bisulfite or ferrous salt solution. The bisulfite or ferrous salt may require some dilute sulfuric acid (10% w/w) to promote reduction. Neutralize with sodium carbonate to neutral pH, if acid was used. Decant or filter and deposit sludge in approved landfill. Where permitted, the sludge may be drained into sewer with large quantities of water.

Option # 2: Absorb with inert media like diatomaceous earth or inert floor dry, collect into a drum and dispose of properly. Do not use saw dust or other incompatible media. Disposal of all materials shall be in full and strict compliance with all federal, state, and local regulations pertaining to permanganates.

To clean contaminated floors, flush with abundant quantities of water into sewer, if permitted by federal, state, and local regulations. If not, collect water and treat as described above.

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Do not allow to enter drains, sewers or watercourses. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling

Take any precaution to avoid mixing with combustibles. Keep away from clothing and other combustible materials. Do not get this material in your eyes, on your skin, or on your clothing. Do not breathe mist or vapor. Use Personal Protective Equipment recommended in section 8 of the SDS. If clothing becomes contaminated, remove and wash off immediately. Spontaneous ignition may occur in contact with cloth or paper. When using, do not eat, drink or smoke. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep container tightly closed and in a well-ventilated place. Store in a cool, dry place. Store away from incompatible materials (See Section 10). Store in accordance with NFPA 430 requirements for Class II oxidizers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Sodium permanganate (CAS 10101-50-5)	Ceiling	5 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Sodium permanganate (CAS 10101-50-5)	TWA	0.1 mg/m3	Inhalable fraction.
		0.02 mg/m3	Respirable fraction.

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Type	Value	Form
Sodium permanganate (CAS 10101-50-5)	TWA	1 mg/m3	Fume.

US NIOSH Pocket Guide to Chemical Hazards: Short Term Exposure Limit (STEL)

Components	Type	Value	Form
Sodium permanganate (CAS 10101-50-5)	STEL	3 mg/m3	Fume.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Follow standard monitoring procedures.

Appropriate engineering controls

Provide adequate general and local exhaust ventilation. An eye wash and safety shower must be available in the immediate work area.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.

Skin protection

Hand protection

Wear chemical-resistant, impervious gloves. Use protective gloves made of: Rubber or plastic. Suitable gloves can be recommended by the glove supplier.

Other	Wear appropriate chemical resistant clothing. Rubber or plastic apron.
Respiratory protection	In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Keep from contact with clothing and other combustible materials. Remove and wash contaminated clothing promptly. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance	Purple. Liquid.
Physical state	Liquid.
Form	Aqueous solution.
Color	Purple.
Odor	Odorless.
Odor threshold	Not available.
pH	5 - 8
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Does not flash.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Miscible with water.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	1299.2 °F (704 °C)
Viscosity	Not available.
Other information	
Density	9.76 lb/gal
Explosive properties	Not explosive. Can explode in contact with sulfuric acid, peroxides and metal powders.
Oxidizing properties	Oxidizer.

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Contact with combustible material may cause fire. Can explode in contact with sulfuric acid, peroxides and metal powders.
Conditions to avoid	Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction.
Incompatible materials	Acids. Peroxides. Reducing agents. Combustible material. Metal powders.
Hazardous decomposition products	By heating and fire, corrosive vapors/gases may be formed. Contact with hydrochloric acid liberates chlorine gas.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Harmful if swallowed.
Inhalation	May cause irritation to the respiratory system.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity	Harmful if swallowed.
Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory sensitization	Not classified.
Skin sensitization	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Not classified.
Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	May cause irritation of respiratory tract.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	Chronic effects are not expected when this product is used as intended. Prolonged exposure, usually over many years, to manganese oxide fume/dust can lead to chronic manganese poisoning, chiefly affecting the central nervous system.

12. Ecological information

Ecotoxicity	Very toxic to aquatic life with long lasting effects.
Persistence and degradability	Expected to be readily converted by oxidizable materials to insoluble manganese oxide.
Bioaccumulative potential	Potential to bioaccumulate is low.
Mobility in soil	The product is miscible with water. May spread in water systems.
Other adverse effects	None known.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Hazardous waste code	D001: Ignitable waste The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Do not allow this material to drain into sewers/water supplies.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Rinse container at least three times to an absence of pink color before disposing. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN3214
UN proper shipping name	Permanganates, inorganic, aqueous solution, n.o.s. (Sodium permanganate)
Transport hazard class(es)	5.1
Subsidiary class(es)	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	26, 353, IB2, T4, TP1
Packaging exceptions	152
Packaging non bulk	202

Packaging bulk 242

IATA

UN number UN3214

UN proper shipping name Permanganates, inorganic, aqueous solution, n.o.s. (Sodium permanganate)

Transport hazard class(es) 5.1

Subsidiary class(es) -

Packaging group II

Environmental hazards Yes

Labels required 5.1

ERG Code 5L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3214

UN proper shipping name PERMANGANATES, INORGANIC, AQUEOUS SOLUTION, N.O.S. (Sodium permanganate)

Transport hazard class(es) 5.1

Subsidiary class(es) -

Packaging group II

Environmental hazards

Marine pollutant Yes

Labels required 5.1

EmS F-H, S-Q

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Drug Enforcement Administration (DEA) (21 CFR 1310.02 (b) 8: List II chemical.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Sodium permanganate (CAS 10101-50-5) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Sodium permanganate	10101-50-5	19 - 21

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Sodium permanganate (CAS 10101-50-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Sodium permanganate (CAS 10101-50-5) 6588

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Sodium permanganate (CAS 10101-50-5) 15 % wt

DEA Exempt Chemical Mixtures Code Number

Sodium permanganate (CAS 10101-50-5) 6588

Food and Drug Administration (FDA) Not regulated.

US state regulations This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Sodium permanganate (CAS 10101-50-5) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

Not regulated.

US. Rhode Island RTK

Sodium permanganate (CAS 10101-50-5)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).


16. Other information, including date of preparation or last revision

Issue date 16-September-2013

Revision date -

Version # 01

NFPA Ratings



List of abbreviations

GHS: Globally Harmonized System of Classification and Labeling of hazardous properties of Chemicals.

TWA: Time weighted average.

LD50: Lethal Dose, 50%.

LC50: Lethal Concentration, 50%.

IMDG: International Maritime Dangerous Goods.

IATA: International Air Transport Association.

MARPOL: International Convention for the Prevention of Pollution from Ships.

References

HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

IARC Monographs. Overall Evaluation of Carcinogenicity

National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change and, therefore, holders and users should satisfy themselves that they are aware of all current data and regulations relevant to their particular use of product. CARUS CORPORATION DISCLAIMS ALL LIABILITY FOR RELIANCE ON THE COMPLETENESS OR ACCURACY OR THE INFORMATION INCLUDED HEREIN. CARUS CORPORATION MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE OR PURPOSE OF THE PRODUCT DESCRIBED HEREIN. All conditions relating to storage, handling, and use of the product are beyond the control of Carus Corporation, and shall be the sole responsibility of the holder or user of the product.

(Carus and design) is a registered service mark of Carus Corporation.